



Parabond V-260

Carpet Pad Adhesive Extremely Flammable

PARABOND ACCESSORIES

DESCRIPTION:

Parabond V-260 Carpet Pad Adhesive is an Extremely Flammable solvent based pad adhesive that is **VOC Compliant** and is recommended for permanently fastening carpet padding over any approved flooring surface. V-260 has good initial tack and high strength to prevent movement of padding during stretching or subsequent use.

V-260 Pad Adhesive is both California and OTC Compliant for VOC's.

NOTE: Due to continuing development of new and different types of backings, padding and methods of application, we recommend that any unfamiliar materials be thoroughly tested before attempting a complete installation.

RECOMMENDED SUBSTRATES:

- Concrete
- APA Approved Plywood
- Terrazzo
- Fiber Cement Underlayment
- Portland Based Patching Underlayments
- Radiant Heated Sub-floors
- Properly prepared VCT (single layer)
- Properly prepared sheet vinyl (single layer)

DIRECTIONS:

1. The floor must be clean, dry, and free of dust, dirt and grease or oil.
2. There is an inner seal under the screw cap on the container that should be removed. Punch a 1/8" diameter hole in this seal.

3. Pour adhesive on the floor in a 3" or 4" bead from the wall. Use a zigzag pattern at the padding seam.
4. Spread adhesive with a thin scrap piece of carpet.
5. Let the adhesive dry two to five minutes.
6. Drop padding into exact position desired and apply pressure by walking over the adhesive area.
7. Install carpet immediately after laying padding. Padding will not slip once placed into adhesive.
8. It is the sole responsibility of the installer to determine the suitability and compatibility of the adhesive for the end user's intended use.

CLEAN-UP:

Parabond M-315 Non-Flammable Cleaner can be used to clean up excess adhesive or spills.

PHYSICAL PROPERTIES:

- Open Time up to 2 hours
- Shelf Life One Year in unopened container
- Color Yellow Brown

PACKAGING:

- One - 1 Gallon Metal Can

WARRANTY:

Royal Adhesives and Sealants offers a limited warranty for this product when used in accordance with printed specifications. A copy of the limited warranty can be obtained by calling technical service at 800-763-7272 or visiting www.parabond.com.