



# Vitex M-620 Primer

## VITEX UNDERLAYMENTS

### DESCRIPTION:

Parabond M-620 Primer is a blend of special polymers and chemical modifiers designed to be used as a primer on porous substrates for Parabond Thick Pour PFU Self Leveling Underlayment. The M-620 Primer may also be used as a substrate primer to enhance bond strength of patching, leveling and skim coating as well as reduction of the porosity of some substrates. Prime standard concrete with Parabond M-620 Primer diluted 1:1 with water. Apply evenly with a medium push broom covering the entire surface avoiding bare spots. Remove puddles and excess primer. Do not use mops or paint rollers for applications.

This product is Not Freeze-Thaw stable, therefore, **PROTECT FROM FREEZING.**

### COVERAGE:

Approximately 250 sq ft / gallon

### SHELF LIFE:

One year @70°F in un-opened container

### FOR MORE INFORMATION READ MATERIAL SAFETY DATA SHEET

### KEEP OUT OF REACH OF CHILDREN

### LIMITATIONS:

1. This product is intended for interior use only.
2. Use underlayment recommended by the floor-covering manufacturer.

3. Do not use on floors where excessive moisture, alkali or hydrostatic pressure is present.
4. We require that moisture tests be performed on all concrete sub-floors regardless of age of slab. Moisture testing should be performed by ASTM F 1869 Calcium Chloride Tests with moisture levels not to exceed (3) pounds per Twenty-four (24) hours per one thousand (1000) square feet or ASTM F 2170 In Situ Relative Humidity Test with readings, not to exceed seventy-five (75) percent.
5. Do not use over expansion joints.
6. Do not use as a concrete resurfacing material that will be left exposed.
7. It is the sole responsibility of the installer to determine the suitability and compatibility of the adhesive for the user's intended use.

### SHAKE WELL

### PROTECT FROM FREEZING

### WARRANTY:

Royal Adhesives and Sealants offers a limited warranty for this product when used in accordance with printed specifications. A copy of the limited warranty can be obtained by calling technical service at 800 763-7272 or visiting [www.parabond.com](http://www.parabond.com)

863 SE Main Street • Simpsonville, SC 29681

Phone: 1-800-763-7272 • ISO 9001 Certified

[www.parabond.com](http://www.parabond.com)

1/7/2014