



# Parabond M-363

## All Purpose Seam Sealer Non Flammable

PARABOND ACCESSORIES

### DESCRIPTION:

Parabond M-363 All-Purpose Seam Sealer is recommended for seaming all carpets with jute or synthetic secondary backing, sponge rubber, high density foam backing (including Dow's Enhancer) and latex unitary.

The M-363 is a must for double stick glue down, direct glue down and stretch-in applications. The M-363 is excellent for bonding tack strip to structurally sound concrete surfaces.

M-363 is **Not Recommended** for use with PVC/Vinyl backed carpeting.

### DIRECTIONS:

1. Prepare carpet according to manufacturer's instructions. Refer to CRI Carpet Installation Standard 2009 for additional information regarding subfloor preparations, etc.
2. Apply a bead of seam adhesive along one side of the trimmed edge where the face yarn enters the backing using an application bottle.
3. Complete the seam by butting both sections of the carpet together while the adhesive is still wet (within 5 minutes).
4. If the seam tends to separate, relieve the stress on the carpet with a knee kicker.
5. Avoid soaking carpet with solvent. Do **Not** pour solvent directly on carpet.
6. For tack strip application, apply a generous bead of adhesive to the back of each piece of strip.
7. Put the tack strip in place, remove briefly, allowing the solvent to flash, then re-install.
8. This will permit the contact bond to gain strength quickly.
9. Allow the adhesive to cure completely before installing the carpet.
10. It is the sole responsibility of the installer to determine the suitability and compatibility of the adhesive for the end user's intended use.

### COVERAGE:

One quart provides approx. 350 linear ft of 1/8" bead.

### CLEAN-UP:

Use Parabond M-315 Reducer/Cleaner to remove wet adhesive from carpet yarn. Adhesive smears on the carpet surface are easily cleaned within ten minutes by gentle daubing/rubbing with a clean white cloth, wet with Parabond M-315.

### FOR PROFESSIONAL USE ONLY

### KEEP OUT OF REACH OF CHILDREN

### FOR MORE INFORMATION READ MATERIAL SAFETY DATA SHEET

### WARRANTY:

Royal Adhesives and Sealants offers a limited warranty for this product when used in accordance with printed specifications. A copy of the limited warranty can be obtained by calling technical service at 800 763-7272 or visiting [www.parabond.com](http://www.parabond.com).

863 SE Main Street • Simpsonville, SC 29681  
Phone: 1-800-763-7272 • ISO 9001 Certified

[www.parabond.com](http://www.parabond.com)

12/19/2013