

SCS Global Services does hereby certify that an independent assessment has been conducted on behalf of:

H.B. Fuller Construction Products/ Royal Adhesives and Sealants

1702 Kimberly Park Dr., Dalton, GA, United States
For the following product(s):

See Addendum

The product(s) meet(s) all of the necessary qualifications to be certified for the following claim(s):

FloorScore®

Indoor Air Quality Certified to SCS-EC10.3-2014 v4.1

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring. Also, conforms to the SCAQMD Rule 1168 - Adhesive and Sealants (October 2017).

Standard Product Application Amount: 308 g/m²

Measured Concentration of Total Volatile Organic Compounds (TVOC): 0.5 – 5.0 mg/m³ (in compliance with CDPH/EHLB Standard Method v1.2-2017)

Methylene Chloride and Perchloroethylene are not intentionally added to certified products.

Registration # SCS-FS-07318

Valid from: November 1, 2023 to September 30, 2024



ANSI National Accreditation Board
ACCREDITED
ISO/IEC 17065
PRODUCT CERTIFICATION
BODY

A handwritten signature in black ink that reads 'Stanley Mathuram'.

Stanley Mathuram, PE, Executive Vice President
SCS Global Services
2000 Powell Street, Ste. 600, Emeryville, CA 94608 USA

Certification Addendum

H.B. Fuller Construction Products/ Royal Adhesives and Sealants

Certification: Registration # SCS-FS-07318 | Valid from: November 1, 2023 to September 30, 2024

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification; certified products are only listed on the SCS Green Products Guide, <http://www.scsglobalservices.com/certified-green-products-guide>.

Addendum **FloorScore®**

Conformance: Indoor Air Quality Certified to SCS-EC10.3-2014 v4.1

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring. Also, conforms to the SCAQMD Rule 1168 - Adhesive and Sealants (October 2017).

Standard Product Application Amount: 308 g/m²

Measured Concentration of Total Volatile Organic Compounds (TVOC): 0.5 – 5.0 mg/m³ (in compliance with CDPH/EHLB Standard

Products: **Pressure Sensitive Adhesives:**

Chapco Safe Set 2, Fortane Universal Pressure Sensitive Adhesive, TEC 744, TEC 749, Fusion Series 5082, Fusion Series 5092, Fusion Series 5092HT, Signature Series 5060, Signature Series 5080, TEC Flexera High Tack Premium Universal Adhesive, TEC Flexera Premium Universal Adhesive